

Product Data Sheet

The catalog is Actual at the date of
30.03.2020



HOLDING SOLENOIDS WITH PERMANENT MAGNET

Manufacturer: SELOS

Product code: 1259

Your price from **8,94 €** Gross



Martin Krechac (EN) B
GSM: +421 901 901 708 Tel.: +421
32 2851 322 E-mail:
systemy@selos.sk

Holding solenoids with power supply 24 VDC. These types of solenoids are used in manipulators, locking systems, etc. Magnetic force is generated by permanent magnet inside – when power supply is switched off. After switching the power supply on (right polarity is required), the electromagnet releases the load. The electromagnets have high holding force and can be combined to multiple systems. These types are suitable for applications where high safety level is required against power failure.

- Nominal power supply 24 VDC \pm 10%
- Duty cycle 15%
- Heat insulation class F
- Protection of the solenoid IP65

| SKU | A | B | Power supply | Holding force | Availability(days) | Weight(kg) | Price incl. VAT |
|------------------|---------|---------|--------------|---------------|--------------------|------------|-----------------|
| ZHI-2016 | 20.0 mm | 16.0 mm | 6 VDC | 10.0 N | 2 | 0.03 | 8,94€ |
| EPPM-2025-24-020 | 20.0 mm | 25.0 mm | 24 VDC | 45.0 N | 2 | 0.06 | 46,49€ |
| EPPM-2529-24-020 | 25.0 mm | 29.0 mm | 24 VDC | 120.0 N | 4 | 0.1 | 47,76€ |
| EPPM-3529-24-020 | 35.0 mm | 29.0 mm | 24 VDC | 300.0 N | 2 | 0.2 | 55,08€ |
| EPPM-4029-24-020 | 40.0 mm | 29.0 mm | 24 VDC | 400.0 N | 2 | 0.25 | 64,27€ |
| EPPM-5029-24-020 | 50.0 mm | 29.0 mm | 24 VDC | 500.0 N | 2 | 0.6 | 70,98€ |
| EPPM-6329-24-020 | 63.0 mm | 29.0 mm | 24 VDC | 960.0 N | 2 | 0.7 | 77,69€ |
| EPPM-8245-24-020 | 82.0 mm | 45.0 mm | 24 VDC | 1900.0 N | 2 | 1.3 | 129,60€ |